

1 UPS 25-50 180



: 96281432

1-

TF

: 2 .. 110 °C  
 : 60 °C  
 983.2 / ³

110  
 : VDE,AAA,EAC

EN-JL1030  
 ASTM 30 B  
 , PES/PP

.T : - 80 0C: 40 °C

10  
 G 1 1/2  
 PN 10  
 180

1: 35  
 2: 45

: 50  
 : 50 Hz  
 : 1 x 230  
 1: 0.16 A

2: 0.2 A  
3: 0.23 A  
- : 2  
(IEC 34-5): IP44  
(IEC 85): F  
:  
:  
:  
:  
C : 2.6  
: 2.8  
: 0.004 <sup>3</sup>  
: RS  
: 8413703000

UPS 25-50 180  
 EAN : 96281432  
 5700830498057

TF : 3  
 50  
 110  
 VDE,AAA,EAC

EN-JL1030  
 ASTM 30 B  
 , PES/PP

.T 80 OC: 40 °C

10  
 G 1 1/2  
 PN 10  
 180

2 .. 110 °C

60 °C

983.2 / ³

1: 35

2: 45

50  
 50 Hz  
 1 x 230  
 1: 0.16 A  
 2: 0.2 A  
 3: 0.23 A

2  
 (IEC 34-5): IP44  
 (IEC 85): F

9H

2.6  
 2.8  
 0.004 ³

C RS  
 8413703000

