

| | | |
|-----|------------------------------|-------------------|
| | | UPSD 32-60 F |
| | | 96408898 |
| EAN | | 5700390916084 |
| | | 3 |
| | | 60 |
| | | AAA,EAC |
| | | EN-JL1040 |
| | | ASTM 35 B - 40 B |
| | | DIN W.-Nr. 1.4301 |
| | | AISI 304 |
| | | 0 .. 40 °C |
| | | 10 |
| | | DIN |
| | | DN 32 |
| | | PN 6 / PN 10 |
| | | 220 |
| | | -10 .. 120 °C |
| | | 60 °C |
| | | 983.2 / 3 |
| | 1: | 170 |
| | 2: | 180 |
| | | 190 |
| | | 50 Hz |
| | | 1 x 230-240 |
| | 1: | 0.84 A |
| | 2: | 0.86 A |
| | 3: | 0.88 A |
| Cos | 1: | 0.88 |
| Cos | 2: | 0.91 |
| Cos | | 0.94 |
| | | 6 /400 |
| | (IEC 85): | F |
| | Enclosure class (IEC 60529): | X4D |
| | | CONTACT |
| | | 12H |
| | | 31.6 |
| | | 35.1 |
| | | 0.04 3 |
| C | | RS |
| | | 8413703000 |

