

| | | |
|------------------------------|-----------|-------------------|
| | | UPS 65-185 F |
| | | 96430298 |
| EAN | | 5700392948113 |
| | | 3 |
| | | 185 |
| | | AAA,EAC |
| | | EN-JL1040 |
| | | ASTM 35 B - 40 B |
| | | DIN W.-Nr. 1.4301 |
| | | AISI 304 |
| | | 0 .. 40 °C |
| | | 10 |
| | | DIN |
| | | DN 65 |
| | | PN 6 / PN 10 |
| | | 340 |
| | | -10 .. 120 °C |
| | | 60 °C |
| | | 983.2 / ³ |
| | 1: | 1220 |
| | 2: | 1340 |
| | | 1710 |
| | | 50 Hz |
| | | 3 x 400-415 |
| | 1: | 2 A |
| | 2: | 2.2 A |
| | 3: | 3.25 A |
| Cos | 1: | 0.88 |
| Cos | 2: | 0.88 |
| Cos | | 0.76 |
| | (IEC 85): | H |
| Enclosure class (IEC 60529): | | X4D |
| | | CONTACT |
| | | 1.30H |
| | | 32.5 |
| | | 33.7 |
| | | 0.055 ³ |
| Danish VVS No.: | | 380738043 |
| C | | RS |
| | | 8413703000 |

