

| | | |
|------------------------------|----|-------------------|
| | | UPSD 65-60/2 F |
| | | 96404981 |
| EAN | : | 5700390739263 |
| | | 3 |
| | | 60 |
| | | AAA,EAC |
| | | EN-JL1040 |
| | | ASTM 35 B - 40 B |
| | | DIN W.-Nr. 1.4301 |
| | | AISI 304 |
| | | 0 .. 40 °C |
| | | 10 |
| | | DIN |
| | | DN 65 |
| | | PN 6 / PN 10 |
| | | 340 |
| | | -10 .. 120 °C |
| | | 60 °C |
| | | 983.2 / 3 |
| 1: | | 450 |
| 2: | | 470 |
| | | 510 |
| | | 50 Hz |
| | | 1 x 230-240 |
| 1: | | 2.15 A |
| 2: | | 2.2 A |
| 3: | | 2.4 A |
| Cos | 1: | 0.91 |
| Cos | 2: | 0.93 |
| Cos | : | 0.92 |
| | | 16 /400 |
| | | 2 |
| (IEC 85): | | H |
| Enclosure class (IEC 60529): | | X4D |
| | | CONTACT |
| | | 12H |
| | | 50 |
| | | 56.9 |
| | | 0.125 3 |
| C | : | RS |
| | | 8413703000 |

