

1 UPS 25-60 180



: 59546800

3-

TF

: 2 .. 110 °C  
 : 60 °C  
 983.2 / ³

110  
 : EAC

EN-JL1030  
 ASTM 30 B  
 , PES/PP

.T : - 80 0C: 80 °C

10  
 G 1 1/2  
 PN 10  
 180

2: 140

: 130  
 : 50 Hz  
 : 3 x 400  
 2: 0.24 A  
 3: 0.21 A

2: 0.3 A  
: 0.31 A  
(IEC 34-5): IP42  
(IEC 85): H  
:  
:  
:  
:  
C : 2.5  
: 2.7  
: 0.004<sup>3</sup>  
: RS  
: 8413703000

UPS 25-60 180  
 EAN : 59546800  
 5700390573621

TF : 2  
 60  
 110  
 EAC

EN-JL1030  
 ASTM 30 B  
 , PES/PP

80 °C

10  
 G 1 1/2  
 PN 10  
 180

2 .. 110 °C

60 °C

983.2 / ³

2: 140

130  
 50 Hz  
 3 x 400

2: 0.24 A  
 3: 0.21 A

2: 0.3 A  
 0.31 A

(IEC 34-5): IP42  
 (IEC 85): H

9H

2.5  
 2.7  
 0.004 ³

C : RS  
 8413703000

