

| | | |
|-----|--|-------------------|
| | | UPS 80-120 F |
| | | 96402440 |
| EAN | | 5700390669447 |
| | | 3 |
| | | 120 |
| | | AAA,EAC |
| | | EN-JL1040 |
| | | ASTM 35 B - 40 B |
| | | DIN W.-Nr. 1.4301 |
| | | AISI 304 |
| | | 0 .. 40 °C |
| | | 6 |
| | | DIN |
| | | DN 80 |
| | | PN 6 |
| | | 360 |
| | | -10 .. 120 °C |
| | | 60 °C |
| | | 983.2 / 3 |

| | | |
|--|----|-------------|
| | 1: | 1000 |
| | 2: | 1100 |
| | | 1500 |
| | | 50 Hz |
| | | 3 x 400-415 |
| | 1: | 1.65 A |
| | 2: | 1.8 A |
| | 3: | 2.75 A |

| | | |
|------------------------------|-----------|---------|
| Cos | 1: | 0.87 |
| Cos | 2: | 0.88 |
| Cos | | 0.79 |
| | (IEC 85): | H |
| Enclosure class (IEC 60529): | | X4D |
| | | CONTACT |

| | | |
|--------------------|--|------------|
| | | 1.30H |
| | | 38.2 |
| | | 38.6 |
| | | 0.055 ³ |
| Norwegian NRF no.: | | 9042452 |
| C | | RS |
| | | 8413703000 |

