

1 UPS 25-20 180



: 59542500

1-

TF

: 2 .. 110 °C  
 : 60 °C  
 983.2 / ³

110  
 : VDE,EAC

EN-JL1030  
 ASTM 30 B  
 , PES/PP

.T : - 80 0C: 80 °C

10  
 G 1 1/2  
 PN 10  
 180

1: 25  
 2: 40

: 65  
 : 50 Hz  
 : 1 x 230  
 1: 0.11 A

2: 0.18 A  
3: 0.26 A  
- : 2  
(IEC 34-5): IP44  
(IEC 85): F  
:  
:  
:  
:  
C : 2.4  
: 2.6  
: 0.004<sup>3</sup>  
: RS  
: 8413703000

UPS 25-20 180  
 EAN : 59542500  
 5700390864644

TF : 3  
 20  
 110  
 VDE,EAC

EN-JL1030  
 ASTM 30 B  
 , PES/PP

80 °C: 80 °C

10  
 G 1 1/2  
 PN 10  
 180

2 .. 110 °C

60 °C

983.2 / ³

1: 25

2: 40

65  
 50 Hz  
 1 x 230

1: 0.11 A

2: 0.18 A

3: 0.26 A

2

(IEC 34-5): IP44

(IEC 85): F

9H

2.4

2.6

0.004 ³

C : RS  
 8413703000

