

| | | |
|------------------------------|----|-------------------|
| | | UPSD 50-120 F |
| | | 96402107 |
| EAN | : | 5700390659639 |
| | | 3 |
| | | 120 |
| | | EAC |
| | | EN-JL1040 |
| | | ASTM 35 B - 40 B |
| | | DIN W.-Nr. 1.4301 |
| | | AISI 304 |
| | | 0 .. 40 °C |
| | | 10 |
| | | DIN |
| | | DN 50 |
| | | PN 6 / PN 10 |
| | | 280 |
| | | -10 .. 120 °C |
| | | 60 °C |
| | | 983.2 / 3 |
| 1: | | 450 |
| 2: | | 530 |
| | | 720 |
| | | 50 Hz |
| | | 3 x 400-415 |
| 1: | | 0.82 A |
| 2: | | 0.94 A |
| 3: | | 1.3 A |
| Cos | 1: | 0.79 |
| Cos | 2: | 0.81 |
| Cos | : | 0.8 |
| (IEC 85): | | H |
| Enclosure class (IEC 60529): | | X4D |
| | | CONTACT |
| | | 12H |
| | | 51.3 |
| | | 53 |
| | | 0.125 3 |
| Norwegian NRF no.: | | 9042518 |
| C | : | RS |
| | | 8413703000 |

