

|     |                              |                      |
|-----|------------------------------|----------------------|
|     |                              | UPS 80-60 F B        |
|     |                              | 96402401             |
| EAN |                              | 5700390668037        |
|     |                              | 3                    |
|     |                              | 60                   |
|     |                              | CE,EAC,AAA,WEEE      |
|     |                              | DIN W.-Nr. 2.1176.01 |
|     |                              | ASTM B-271           |
|     |                              | DIN W.-Nr. 1.4301    |
|     |                              | AISI 304             |
|     |                              | 0 .. 40 °C           |
|     |                              | 10                   |
|     |                              | DIN                  |
|     |                              | DN 80                |
|     |                              | PN 10                |
|     |                              | 360                  |
|     |                              | -10 .. 120 °C        |
|     |                              | 60 °C                |
|     |                              | 983.2 / 3            |
|     | 1:                           | 470                  |
|     | 2:                           | 570                  |
|     |                              | 880                  |
|     |                              | 50 Hz                |
|     |                              | 3 x 400-415          |
|     | 1:                           | 0.84 A               |
|     | 2:                           | 1 A                  |
|     | 3:                           | 1.8 A                |
| Cos | 1:                           | 0.81                 |
| Cos | 2:                           | 0.82                 |
| Cos |                              | 0.71                 |
|     | (IEC 85):                    | H                    |
|     | Enclosure class (IEC 60529): | X4D                  |
|     |                              | CONTACT              |
|     |                              | 1.30H                |
|     |                              | 43.2                 |
|     |                              | 44.3                 |
|     |                              | 0.055 3              |
| C   |                              | RS                   |
|     |                              | 8413703000           |

