

1 UPSD 32-80 180



: 95906455

, PES/PP.

1-

: -25 .. 110 °C  
 : 60 °C  
 : 983.2 / 3

TF

: 110  
 : EAC

EN-JL1030  
 ASTM 30 B  
 , PES/PP

.T : - 80 0C: 40 °C

: 10  
 : G 2  
 : PN 10  
 : 180

:  
 1: 135  
 2: 200

: 220  
 : 50 Hz  
 : 1 x 230

1: 0.6 A  
2: 0.9 A  
3: 0.98 A  
- : 4  
(IEC 34-5): X2D  
(IEC 85): F  
:  
:  
:  
C : 10.8  
: 11.3  
: 0.015<sup>3</sup>  
: RS  
: 8413703000

UPSD 32-80 180	
95906455	
EAN : 5700310353951	
3	
80	
TF : 110	
EAC	
EN-JL1030	
ASTM 30 B	
, PES/PP	
40 °C	
10	
G 2	
PN 10	
180	
-25 .. 110 °C	
60 °C	
983.2 / ³	
1: 135	
2: 200	
220	
50 Hz	
1 x 230	
1: 0.6 A	
2: 0.9 A	
3: 0.98 A	
4	
(IEC 34-5): X2D	
(IEC 85): F	
CONTACT	
12H	
10.8	
11.3	
0.015 ³	
C : RS	
8413703000	

